

Integrated LCD Linux Thin Clients

TeleCLIENT TC5550

Integrated LCD Linux TeleCLIENT

- Integrated with a Crisp, Clear 15" TFT LCD
- Powerful 1 GHz CPU, High Performance Linux Thin Client
- 24bit Graphic Support
- Native X Windows, RDP, and ICA Protocols included
- Terminal Emulators and 802.11b Wireless Available
- Mozilla Browser With Plug In Support





TeleCLIENT - TC5550

Integrated LCD Linux Thin Clients

- Linux operating system providing multiple protocol support
- VESA standard holes for multiple protocol support
- Terminal emulations available to connect to legacy hosts
- Designed for long shelf life
- Provides protections against software corruption or virus attacks

TECHNICAL SPECIFICATIONS

MODELS

- TC5550** 15" LCD Integrated thin client
TC5550i with terminal emulations
TC5550L with wireless 802.11b
TC5550Li with terminal emulation and 802.11b wireless LAN

HARDWARE

- Display** 15" Digital TFT LCD Display up to
TC5550 1024x768 resolution and 24-bit true color
- CPU** Transmeta Crusoe 1GHz x86 base CPU
- RAM** 128MB RAM
- Flash Memory** 32MB Flash
- Resolution Support** SMI display controller
- Audio** NS Audio CODEC with full 16-bit stereo out, Mic in
- Device Ports** 1 Parallel Port
 2 Serial Ports
 2 PS/2 Ports - 1 keyboard & 1 mouse included
 Audio Ports - 1 microphone in
 1 audio out

NETWORK AND COMMUNICATIONS

- Network Protocols** 10/100 BaseT Ethernet, 802.11b
 Wireless LAN *, TCP/IP, DNS, DHCP, PPP, SNMP, SNT, PPTP, VPN

SOFTWARE

Client Operating Systems

Linux Kernel 2.4

Server Operating Systems-Compatibility

Microsoft Windows 2003 Server
 Microsoft Windows 2000 Server
 Citrix Metaframe XP products
 Unix Server

Software Add Ons

Microsoft RDP 5
 ICA 7

Pericom teemtalk2000 emulations

TeleVideo 910, 925, 950, 955
 Digital VT52, 100, 220, 320, 420, 520
 IBM 3151, 3270E, 5250E
 Hewlett Packard 2392A, 2622A, 700/92
 Wyse 50, 50+, 60
 SCO Console
 ANSI-BBS
 AixTerm
 AT386
 ADDS A2
 Hazeltine 1500

Mozilla Browser
 JVM
 ThinPrint

MOUNTING OPTIONS

- TC5550 Desktop** 75mmx75mm
 VESA standard mounting holes
 or
 100mmx100mm
 VESA standard mounting holes
- TC5550 Wall/Arm** 75mmx75mm
 VESA standard mounting holes

ENVIRONMENTAL

- Operating Temperature** 32°F to 104°F (0° to 40°C)
Storage Temperature -4°F to 140°F (-20° to 60°C)
Humidity 20% to 85% no condensing
Operating Altitud 0 to 10,000 feet (3,048 meters)

PHYSICAL SPECIFICATIONS

- TC5550**
- Height** 15.7 inches (39.9 cm)
Width 15.1 inches (38.4 cm)
Depth 10.6 inches (36.9 cm)
Weight 10.5 lbs (4.8 kg)

POWER SPECIFICATIONS

- TC5550** 100-240v 60/50Hz, 4.58A, 28W max

REGULATORY COMPLIANCE

- FCC Class B** CE

WARRANTY

- 1 year** - Standard
 Additional 2 years available for purchase

TeleVideo, Inc.

2345 Harris Way,
 San Jose, CA 95131
 Tel: 408.954.8333
 Fax: 408.954.0623

www.televideo.com
info@televideo.com

Sales
telesales@televideo.com

Technical Support
ts_support@televideo.com
 Tel: 408.955.7711



The TeleVideo name and logo are registered trademarks. All other names referenced are the service mark, trademark or registered trademarks of their respective owners. All specifications are subject to change without prior notice. TeleVideo reserves the right to change specifications without notice. TeleVideo is not liable for any information, typographical errors or omissions. Printed in USA Copyright 2002 TeleVideo, Inc.

Microsoft, Windows, and Windows NT, CE, XPe are registered trademarks of Microsoft Corporation. Citrix, WinFrame, MetaFrame, NFuse, and ICA are registered trademarks of Citrix Systems, Inc. All other products are trademarks and/or registered trademarks of their respective companies. *Optional