

Wireless Web Tablet Thin Clients

TeleCLIENT MC3000

Wireless Web Tablet Thin Clients

- Bright 10.4" Touchscreen LCD display
- 802.11b Wireless LAN
- Windows® CE.NET Operating System
- Configure as Windows-Based Terminal or CE desktop
- Citrix® ICA, Microsoft® RDP and Terminal Emulation
- Lightweight, Rechargeable Battery, USB





TeleCLIENT MC3000

Wireless Web Tablet Thin Clients

- Portable and lightweight
- Wireless connection to applications and the Internet
- Bright LCD touchscreen display with soft keyboard
- No moving parts
- Energy efficient
- Lower TCO and greater ROI
- Improve point-of-service and point-of-care functions

TECHNICAL SPECIFICATIONS

CONFIGURATION

Windows Based-Terminal or
Windows CE desktop

HARDWARE

CPU

300 MHz processor

RAM Memory

64MB SDRAM

Flash Memory

32MB Compact Flash

Display

10.4 inch, TFT LCD at 800x600 SVGA resolution, touch sensitive, built-in stylus and on screen soft keyboard

Graphics Support

Integrated graphics co-processor, 4,8, and 16 bit support

Audio Support

Full 16 Bit stereo sound with built-in speaker, microphone and headphone jacks

NETWORKING & COMMUNICATIONS

Networking Protocols

Built-in 2.4 GHz Wireless LAN IEEE 802.11b module (up to 11 Mbps)

Communication Protocols

Microsoft RDP 5.1 and Citrix ICA 6.30

Ports

1 USB port
1 external CompactFlash™ slot

SOFTWARE

Operating System

Windows CE.NET

Server Operating Systems and Software

Microsoft Windows2000 Server Terminal Services, NT Server 4.0 TSE, Citrix MetaFrame, MetaframeXP, WinFrame, Windows .NET server, Citrix NFuse, TeleMANAGER Remote Management Software with MMC support

Web Access/Browser and Application Support

Microsoft Internet Explorer 5.5, Windows Media Player, Java Virtual Machine™, Acrobat® PDF Viewer, Macromedia Flash™ Player, Microsoft Office Suite Viewer

Audio: MP3, WAV, AIFF, MIDI, AU formats

Terminal Emulations

TVI925*, 990*, 995-65*, IBM 3270, 3270E, 3287, 5250, DEC VT52, 100, 220, 320, 420, UNIX, SCO, Wyse50, 50+, 60, Hazeltine 1500, ADDS A2

Printer Support

Thin Print 5.0*, LPD

Storage Device Support

USB external floppy disk drive*

POWER

12 VDC 30 Watts, 120 Volt AC/DC Adapter
Built-in rechargeable Lithium-Ion battery
Charging stand/cradle

PHYSICAL SPECIFICATIONS

Height: 9.1 inches (23.1cm)

Width: 10.6 inches (26.9cm)

Depth: 0.96 inches (2.4cm)

Weight: 3 lbs (1.3kg) excludes AC/DC adapter and charging stand/cradle

STANDARD PACKAGE & ACCESSORIES

MC3000 Unit with Lithium-Ion Battery Back
Battery charging stand/cradle and AC/DC Adapter
Protective jacket (Blue)
Quick start guide

ENVIRONMENTAL/COMPLIANCE

Operating Temperature

30° ~ 104° F (0° ~ 40° C)

Humidity


0% ~ 90%

FCC-B

CE

WARRANTY

1 year standard



www.televideo.com
info@televideo.com

TeleVideo, Inc.

2345 Harris Way,
San Jose, CA 95131
Tel: 408.954.8333
Fax: 408.954.0623

U.S. and Canada Sales
telesales@televideo.com

Technical Support
ts_support@televideo.com
Tel: 408.955.7711



TeleVideo®
PIONEERS IN NETWORK COMPUTING

The TeleVideo name and logo are registered trademarks. All other names referenced are the service mark, trademark or registered trademarks of their respective owners. All specifications are subject to change without prior notice. TeleVideo reserves the right to change specifications without notice. TeleVideo is not liable for any information, typographical errors or omissions. Printed in USA Copyright 2002 TeleVideo, Inc.

Microsoft, Windows, and Windows NT, CE, XPe are registered trademarks of Microsoft Corporation. Citrix, WinFrame, MetaFrame, NFuse, and ICA are registered trademarks of Citrix Systems, Inc. All other products are trademarks and/or registered trademarks of their respective companies. *Optional